

A cost-efficient, robust solution that gives you the benefit of high productivity and savings

The SimPact 4T-R filter has a compact, cylindrical design and an efficient pulse-jet cleaning system. The filter housing and inlet zone are strategically placed in the various construction forms. This ensures a smooth flow of both coarse and fine particles into the filter.

Benefits

Efficiency


- The pulse jet system automatically cleans the bags row-by-row even as the dust is being filtered. The advantage is that the filter continues to work for you while the bags are being cleaned.

Savings

- Being a low maintenance solution, the SimPact 4T-R needs minimum downtime. This means continuous plant operations for you.
- The filter control system helps maintain a low pressure drop – helping you save both compressed air and energy.

Flexibility

- You can separate almost any kind of dust – fine, abrasive or explosive.
- The flexibility in bag removal allows you to easily service the bags.



Features

- Capacity: 500 – 130.000 m³/h
- Filter size: 3,1 – 435,6 m² filter surface
- Standard 5% vacuum
- Pressure shock resistance: Up to 2,0 bar
- Works on both dry and sticky products
- Bag removal: via both clean and dirty air sides
- Complying with the ATEX directive
- Indoor installation with explosion vent following European standard EN14491 or the German guidelines VDI 3673

Construction forms

- Inlets:**
- 03 + 3 WB
 - 04
 - 05
 - 12 (high capacity)
 - 14 (high capacity)
 - 17 + 17 WB (high capacity)

- Top:**
- 4T-R
 - 4T1-R
 - 4T2-R
 - 4T3-R

Applications

- | | | | |
|---|---|---|--|
| <ul style="list-style-type: none">• Grain and feed industry• Chemical industry• Cement industry• Food industry | <ul style="list-style-type: none">• Brewery• Paper industry• Plastics industry• Metal industry | <ul style="list-style-type: none">• Fish feed industry• Pet-food industry• Recycling industry• Wood industry | <ul style="list-style-type: none">• Mineral industry• Fertilizer industry |
|---|---|---|--|

Selecting filter size

SimPact® 4T-R		Filter area m ²												
Type JM	7	10	14	21	32	41	52	70	90	124	146	170	198	
Bag length - dm	10	3,1	4,4	6,2	9,2	14,1	18,0	22,9	30,8	39,6	-	-	-	-
	15	4,6	6,6	9,2	13,9	21,1	27,0	34,3	46,2	59,4	81,8	96,4	112,2	130,7
	20	6,2	8,8	12,3	18,5	28,1	36,1	45,7	61,6	79,2	109,1	128,5	149,6	174,2
	25	-	11,0	15,4	23,1	35,2	45,1	57,2	77,0	99,0	136,4	160,6	187,0	217,8
	30	-	13,2	18,5	27,7	42,2	54,1	68,6	92,4	118,8	163,7	192,7	224,4	261,4
	35	-	15,4	21,6	32,3	49,3	63,1	80,0	107,8	138,5	191,0	224,8	261,8	304,9
	40	-	-	-	36,9	56,3	72,1	91,5	123,2	158,3	218,2	257,0	299,2	348,5
	45	-	-	-	41,6	63,3	81,1	102,9	138,5	178,1	245,5	289,1	336,6	392,0
	50	-	-	-	46,2	70,4	90,2	114,4	153,9	197,9	272,8	321,2	374,0	435,6

For larger filter sizes, please contact Simatek's sales department

Selecting construction form

03 and 03 WB*	04	05	12	14	17 and 17 WB*
Dust load:					
<50 g/m ³	<50 g/m ³	<50 g/m ³	<1000 g/m ³	<100 g/m ³	Unlimited

*) Wide-Body

Selecting the top cover for the clean-air chamber

4T-R	4T1-R	4T2-R	4T3-R
<ul style="list-style-type: none"> • Pressure-shock resistant • Side Removal • Installation of bags through the man door 	<ul style="list-style-type: none"> • Non-pressure shock resistant • Top Removal • Installation of bags from the clean-air side 	<ul style="list-style-type: none"> • Pressure-shock resistant top with hinged cover • Top Removal • Installation of bags from the clean-air side 	<ul style="list-style-type: none"> • Pressure-shock resistant "Walk in plenum" (Penthouse) • Top Removal • Installation of bags from the clean-air side